

Disc-Axe Type Pneumatic Precision Planters



Designed for precise seed placement, this pneumatic seeder delivers high performance across various soil conditions. Its double-disc structure clears residue by slicing through plant debris, while the vacuum system picks up seeds one by one and drops them into the furrow. Adjustable depth wheels and the “V”-type press wheel ensure consistent seed placement and firm soil contact. The result is uniform emergence, straight rows, and an ideal foundation for a productive season





Model	Number of Units	Distance Between Rows	Total Length (cm)	Height (cm)	Width (cm)	Power Requirement (Hp)	Weight (Kg)
REGINA-4	4	45-75	200	160	280	60-65	950
REGINA-5	5	45-75	200	160	320	65-75	1020
REGINA-6	6	45-75	200	160	400	70-75	1250
REGINA-8	8	45-75	200	160	560	95-100	1300
REGINA-12	12	45	200	160	560	160-165	2400
REGINA-4G	4	45-75	200	160	280	60-65	1180
REGINA-5G	5	45-75	200	160	320	65-75	1365
REGINA-6G	6	45-75	200	160	400	70-75	1550
REGINA-8G	8	45-75	200	160	560	95-100	2070
REGINA-12G	12	45	200	160	560	160-165	3150

Universal & Mechanical Seeders (Grain Seeders)

...

COMBINED GRAIN SEEDER is a machine hung and towed with a tractor which deposits wheat, barley, oats, sunflower, lentils, chickpeas, beans and similar seeds and fertilizer to the soil in the desired amount and depth uninterruptedly.



TEKNİK ÖZELLİKLER 142 MM
TECHNICAL SPECIFICATIONS

Mechanical Seeders

MAKİNA CİNSİ TYPE OF MACHINE	İŞ GENİŞLİĞİ WORK WIDTH	İZ GENİŞLİK TRACK WIDTH	MAKİNA YÜKSEKLİĞİ TOTAL HEIGHT	TOPLAM UZUNLUK TOTAL LENGTH	TOHUM KAPASİTESİ SEED CAPACITY	GÜBRE KAPASİTESİ FERTILIZER CAPACITY	TEKERLEK ÖLÇÜLERİ TYRE SIZE	TOPLAM AĞIRLIK TOTAL WEIGHT	GEREKLİ GÜÇ (HP) TRACTOR POWER
20	2840 mm	3620 mm	1450 mm	3050 mm	400 kg	300 kg	750/16	1120 kg	60+
22	3130 mm	3900 mm	1450 mm	3050 mm	430 kg	330 kg	750/16	1232 kg	60+
24	3400 mm	4250 mm	1450 mm	3050 mm	460 kg	360 kg	750/16	1344 kg	70+
28	3980 mm	4820 mm	1450 mm	3050 mm	520 kg	420 kg	750/16	1420 kg	80+



TEKNİK ÖZELLİKLER 125 MM
TECHNICAL SPECIFICATIONS

Mechanical Seeders

TEKNİK ÖZELLİKLER 125 MM - TECHNICAL SPECIFICATIONS

MAKİNA CİNSİ TYPE OF MACHINE	İŞ GENİŞLİĞİ WORK WIDTH	İZ GENİŞLİK TRACK WIDTH	MAKİNA YÜKSEKLİĞİ TOTAL HEIGHT	TOPLAM UZUNLUK TOTAL LENGTH	TOHUM KAPASİTESİ SEED CAPACITY	GÜBRE KAPASİTESİ FERTILIZER CAPACITY	TEKERLEK ÖLÇÜLERİ TYRE SIZE	TOPLAM AĞIRLIK TOTAL WEIGHT	GEREKLİ GÜÇ (HP) TRACTOR POWER
20	2500mm	3300 mm	1450 mm	3050 mm	370 kg	270 kg	750/16	1100 kg	50+
22	2750 mm	3550 mm	1450 mm	3050 mm	400 kg	300 kg	750/16	1210 kg	60+
24	3000 mm	3800 mm	1450 mm	3050 mm	430 kg	330 kg	750/16	1320 kg	60+
28	3500 mm	4300 mm	1450 mm	3050 mm	490 kg	390 kg	750/16	1540 kg	80+
32	4000 mm	4800 mm	1450 mm	3050 mm	550 kg	450 kg	750/16	1760 kg	80+
36	4500 mm	5700 mm	1500 mm	3050 mm	550 kg	470 kg	12.4-11.24	1890kg	80+
40	5000 mm	6200 mm	1500 mm	3150 mm	610 kg	525 kg	12.4-11.24	2100 kg	80+
44	5500 mm	6700 mm	1500 mm	3150 mm	670 kg	580 kg	12.4-11.24	2310 kg	90+
48	6000 mm	7200 mm	1500 mm	3150 mm	730 kg	630kg	12.4-11.24	2520 kg	90+



TEKNİK ÖZELLİKLER 150 MM
TECHNICAL SPECIFICATIONS

Universal Seeders

MAKİNA CİNSİ TYPE OF MACHINE	İŞ GENİŞLİĞİ WORK WIDTH	İZ GENİŞLİK TRACK WIDTH	MAKİNA YÜKSEKLİĞİ TOTAL HEIGHT	TOPLAM UZUNLUK TOTAL LENGTH	TOHUM KAPASİTESİ SEED CAPACITY	GÜBRE KAPASİTESİ FERTILIZER CAPACITY	TEKERLEK ÖLÇÜLERİ TYRE SIZE	TOPLAM AĞIRLIK TOTAL WEIGHT	GEREKLİ GÜÇ (HP) TRACTOR POWER
24	3600 mm	4680 mm	1500 mm	3050 mm	480 kg	370 kg	12.4-11.24	1480 kg	70+
36	5400 mm	6480 mm	1500 mm	3150 mm	670 kg	540 kg	12.4-11.24	2160 kg	80+
40	6000 mm	7080 mm	1500 mm	3150 mm	740 kg	600kg	12.4-11.24	2400 kg	80+

