

MOUNTED FIELD SPRAYER

COMPACT AND DURABLE PROTECTION

Designed for small to medium-sized agricultural operations, the Mounted Field Sprayer offers a perfect balance of durability and efficiency. Connected directly to the tractor's three-point hitch, this machine is lightweight yet robust, thanks to its high-quality polyethylene tank which is resistant to corrosion and UV rays. Equipped with a high-pressure membrane pump, it ensures uniform chemical application, protecting your crops effectively while optimizing chemical usage.

Key Advantages:

- **Durable Construction:** The impact-resistant polyethylene tank ensures a long service life and easy cleaning.
- **High Pressure Performance:** The reliable membrane pump delivers consistent pressure for thorough coverage.
- **Versatile Boom Options:** Available with manual booms ranging from 10m to 12m, equipped with long-lasting brass nozzles.
- **Easy Operation:** Simple connection to the tractor PTO (540 rpm) makes it user-friendly and quick to deploy.
- **Cost-Effective:** An ideal solution for farmers seeking high performance with low maintenance costs.



EQUIPMENTS DESCRIPTIONS		GAFS-400	GAFS-600	GAFS-800	GAFS-1000
TANK	CAPACITY	400 LT	600 LT	800 LT	1000 LT
	MATERIAL	POLYETHYLENE	POLYETHYLENE	POLYETHYLENE	POLYETHYLENE
	COLOUR	GREEN	GREEN	GREEN	GREEN
PUMP	PRESSURE	50 BAR	50 BAR	50 BAR	50 BAR
	FLOW	80 LT / MIN	80LT/MIN	80 LT / MIN	80 LT /MIN
	TYPE	MEMBRANE	MEMBRANE	MEMBRANE	MEMBRANE
POWER	P.T.O	540 R.P.M	540 R.P.M	540 R.P.M	540 R.P.M
CHASSIS	TYPE	TRACTOR MOUNTED	TRACTOR MOUNTED	TRACTOR MOUNTED	TRACTOR MOUNTED
		PAINTED FRAME	PAINTED FRAME	PAINTED FRAME	PAINTED FRAME
REGULATOR	TYPE	C-50/VDR 50	C-50/VDR 50	C-50/VDR 50	C-50/VDR 50
SPRAYING BOOM	TYPE	MANUAL	MANUAL	MANUAL	MANUAL
	LENGHT	10 MT	12 MT	12 MT	12 MT
	NOZZLE QTY	20	24	24	24
	NOZZLE TYPE	BRASS NOZZLE	BRASS NOZZLE	BRASS NOZZLE	BRASS NOZZLE

TRAILED FIELD SPRAYER

HIGH CAPACITY AND ELECTRONIC PRECISION

The Trailed Field Sprayer (GATFS series) is the definitive solution for large-scale professional farming, engineered for massive coverage and exceptional operational precision. Available in high-capacity models (2000L and 3000L), this sprayer significantly reduces downtime for refilling. The core advantage lies in its comprehensive Electronic Remote Control system, which allows the operator to manage all spraying functions, including the hydraulic boom (up to 24 meters), directly and safely from the tractor cabin. Equipped with a powerful membrane pump and an anti-drip nozzle system, the GATFS series guarantees uniform chemical application across vast fields.

Key Advantages:

- **Superior Capacity:** Large polyethylene tanks (2000 LT and 3000 LT) enable extended operation, maximizing productivity.
- **Electronic Control:** Full electronic remote control ensures instant and precise management of the entire spraying process.
- **Advanced Boom System:** Stable, wide-span "Birdwing" type boom (up to 24 MT) features electronic opening and up/down movement for optimal field coverage.
- **Safety & Hygiene:** Separate hand wash and clean water tanks are standard, enhancing operator safety and simplifying system cleaning.
- **Precision Application:** 3-way anti-drip plastic nozzles prevent chemical leakage and dripping, ensuring exact dosage and environmental protection.
- **Premixer Availability:** An optional premixer is available, allowing for easy and safe preparation of chemical mixtures.

EQUIPMENTS	DESCRIPTIONS	GATFS-2000-ELECTRONIC
TANK	CAPACITY	2000 LT
	MATERIAL	POLYETHYLENE
	COLOUR	GREEN
	TYPE	HAND WASH, CLEAN WATER AND MAIN TANK
PUMP	PRESSURE	50 BAR
	FLOW	145 LT/MIN
	TYPE	MEMBRANE PUMP WITH 4 MEMBRANE
POWER	PIQ	540 RPM
CHASSIS	TYPE	TRACTOR TRAILED
		PAINTED FRAME
COMMAND	TYPE	ELECTRONIC REMOTE CONTROL
WHEEL	TYPE	HIGH WHEEL
PREMIXER		OPTIONAL
SPRAYING BOOM	TYPE	ELECTRONIC OPENING/ UP AND DOWN
	LENGHT	16 MT
	NOZZLE QTY	32
	NOZZLE TYPE	3 WAY ANTIDRIPP NOZZLE / PLASTIC

EQUIPMENTS	DESCRIPTIONS	GATFS-3000-ELECTRONIC
TANK	CAPACITY	3000 LT
	MATERIAL	POLYETHYLENE
	COLOUR	GREEN
	TYPE	HAND WASH, CLEAN WATER AND MAIN TANK
PUMP	PRESSURE	50 BAR
	FLOW	145 LT/MIN
	TYPE	MEMBRANE PUMP WITH 4 MEMBRANE
POWER	PTO	540 RPM
CHASSIS	TYPE	TRACTOR TRAILED
		PAINTED FRAME
WHEEL		HIGH WHEEL
COMMAND	TYPE	ELECTRONIC REMOTE CONTROL
PREMIXER		AVAILABLE
SPRAYING BOOM	TYPE	BIRDWING TYPE
		ELECTRONIC OPENING/ UP AND DOWN
	LENGHT	24 MT
	NOZZLE QTY	48
	NOZZLE TYPE	3 WAY ANTIDRIPP NOZZLE / PLASTIC



HIGH-PERFORMANCE FERTILIZER SPREADERS

BOOST YOUR YIELD

The demands of modern agriculture are directly tied to precise and homogeneous fertilization. Delivering the necessary nutrients to your soil at the right time, in the right quantity, and with maximum efficiency is the key to maximizing both your crop quality and total yield.

Designed with years of experience and advanced engineering knowledge, our Fertilizer Spreader series is developed to meet this critical need for farming businesses of all sizes. With a wide range spanning from our compact 300-liter models to large-capacity 2500-liter hydraulic and mechanical models ideal for extensive areas, you can find the perfect solution for your operation, whether you're working in a vineyard or across vast cereal fields.

Our Core Advantages:

- **Durable Construction:** Use of high-quality materials and chrome-plated discs for resistance to heavy-duty conditions and all types of weather.
- **Precise Adjustment:** Easy calibration and adjustment mechanisms allow you to achieve the ideal spreading width and accurate dosage.
- **Wide Working Area:** Working widths ranging from 6 meters up to 36 meters, ensuring significant savings in time and fuel.
- **Model Versatility:** Flexibility to choose between Mechanical, Hydraulic, or Mounted types to ensure the best compatibility with your tractor.

Invest in your future and take control of your fertilization.



350 LT CONICAL FERTILIZER SPREADER		
DESCRIPTIONS	UNIT / TYPE	LSFS350
CAPACITY	LT	350
LENGTH	CM	1000
WIDTH	CM	960
HEIGHT	CM	1360
WEIGHT	KG	82
WORKING WIDTH	MT	16



FERTILIZER SPREADER					
DESCRIPTIONS	UNIT / TYPE	LSFS 400	LSFS 500	LSFS 600	LSFS 800
CAPACITY	LT	400	500	600	800
MODEL		MOUNTED	MOUNTED	MOUNTED	MOUNTED
TYPE		MECHANICAL	MECHANICAL	MECHANICAL / HYDRAULIC	MECHANICAL / HYDRAULIC
LENGTH	CM	114	140	148	165
WIDTH	CM	103	106	112	115
HEIGHT	CM	111	121	125	129
WEIGHT	KG	120	135	140	170
DISC		PAINTED/ CHROME	PAINTED/ CHROME	PAINTED/ CHROME	PAINTED/ CHROME
	PCS	1	1	1 OR 2	2
WORKING WIDTH	MT	18	18	18	18



1000/1200/ 1500 LT FERTILIZER SPREADER				
DESCRIPTIONS	UNIT / TYPE	LSFS 1000	LSFS 1200	LSFS 1500
CAPACITY	LT	1000	1200	1500
MODEL		MOUNTED	MOUNTED	MOUNTED
TYPE		MECHANICAL/ HYDRAULIC	MECHANICAL/ HYDRAULIC	MECHANICAL/ HYDRAULIC
LENGTH	CM	180	185	190
WIDTH	CM	117	235	238
HEIGHT	CM	133	142	160
WEIGHT	KG	210	395	408
DISC		PAINTED/CHROME	PAINTED/CHROME	PAINTED/CHROME
	PCS	2	2	2
WORKING WIDTH	MT	24	36	36

2500 LT TRAILED TYPE FERTILIZER SPREADER

DESCRIPTIONS	UNIT / TYPE	LSFS2500
CAPACITY	LT	2500
MODEL		TRAILED
TYPE	HYDRAULIC	HYDRAULIC
LENGTH	CM	263
WIDTH	CM	258
HEIGHT	CM	228
WEIGHT	KG	770
DISC		CHROME
	QTY	2
WORKING WIDTH	MT	36

